

View Online at <https://aerobasegroup.com/nsn/5340-00-827-4417>

First Leg Length:

Between 0.615 inches and 0.635 inches

Second Leg Length:

Between 0.990 inches and 1.010 inches

Reinforcement Method (non-core):

Beaded both sides

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.194 inches and 0.214 inches

Second Leg Hole Diameter:

Between 0.118 inches and 0.138 inches

Second Leg Distance Between Hole Centers Along Length:

0.365 mils and 0.385 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.053 inches and 0.073 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.240 inches and 0.260 inches

Second Leg End Radius:

Between 0.240 inches and 0.260 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0