NSN 5340-00-828-1411

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-828-1411

| Fabrication Method (non-core): |
|--|
| Machined |
| First Leg Length: |
| 0.810 inches |
| Second Leg Length: |
| 0.950 inches |
| Second Leg Width: |
| 0.500 inches |
| First Leg Hole Diameter: |
| 0.281 inches |
| Second Leg Hole Diameter: |
| 0.219 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.250 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.250 inches |
| First Leg Thickness: |
| 0.059 inches |
| Second Leg Thickness: |
| 0.059 inches |
| First Leg Width: |
| 0.500 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.250 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.250 inches |
| First Leg End Radius: |
| 0.375 inches |
| Second Leg End Radius: |
| 0.375 inches |
| First Leg Style: |
| End radius |
| First Leg Hole Arrangement Style: |
| One hole |
| Second Leg Style: |
| End radius |
| Second Leg Hole Arrangement Style: |
| One hole |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |

90.0 degrees

NSN 5340-00-828-1411 Angle Bracket - Page 2 of 2



| Material: |
|--|
| Steel comp 410 |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Style Designator: |
| Angle |
| Fsc Application Data: |
| Engine, adct, turbo-fan |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A042a0