NSN 5340-00-831-2043

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-831-2043

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Hole Diameter:

0.204 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

Second Leg Slot Length:

Between 0.560 inches and 0.620 inches

Second Leg Slot Width:

Between 0.200 inches and 0.220 inches

First Leg Thickness:

Between 0.073 inches and 0.083 inches

Second Leg Thickness:

Between 0.073 inches and 0.083 inches

Center Section Thickness:

Between 0.073 inches and 0.083 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg End Radius:

0.360 inches

Second Leg End Radius:

Between 0.360 inches and 0.400 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

NSN 5340-00-831-2043

Double Angle Bracket - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0