

View Online at <https://aerobasegroup.com/nsn/5340-00-831-8100>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.740 inches and 0.860 inches

Second Leg Length:

Between 2.360 inches and 2.480 inches

Reinforcement Method (non-core):

Beaded both sides

Second Leg Width:

Between 1.500 inches and 1.600 inches

Second Leg Corner Radius:

Between 0.260 inches and 0.340 inches

First Leg Hole Diameter:

Between 0.213 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.336 inches and 0.350 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.240 inches and 1.260 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.340 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.870 inches and 0.970 inches

First Leg Corner Radius:

Between 0.260 inches and 0.340 inches

First Leg Distance Between Hole Centers Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.340 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0