NSN 5340-00-831-8103

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-831-8103

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Length:

Between 1.660 inches and 1.720 inches

Second Leg Width:

Between 1.580 inches and 1.620 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Hole Diameter:

Between 0.213 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.337 inches and 0.350 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.340 inches and 1.360 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.610 inches and 0.680 inches

First Leg Width:

Between 0.850 inches and 0.890 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.610 inches and 0.680 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

NSN 5340-00-831-8103 Angle Bracket - Page 2 of 2



| Second Leg Relationship To First Leg: |
|---|
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Material: |
| Steel comp 321 |
| Material Specification: |
| Ams 5510 assn standard single material response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A042a0