NSN 5340-00-832-8046

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-832-8046

Flat Hole Diameter: 0.312 inches Width: 3.000 inches Edge Shape: Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Width: 3.000 inches Edge Shape: Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Width: 3.000 inches Edge Shape: Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
3.000 inches Edge Shape: Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Edge Shape: Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Irregular, flat sides, radii ends, two holes Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Length: 5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
5.620 inches Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Corner Radius: 0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
0.620 inches Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Distance Between Holes Along Length: 4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
4.750 inches Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Body Thickness: 0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
0.310 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Securing Device Type: Threaded fastener Mounting Opening Shape Style:
Threaded fastener Mounting Opening Shape Style:
Mounting Opening Shape Style:
Unthreaded hole
Special Features:
Two fins on underside of cover, 1.620 in. Lg, 1.000 in. W, 0.180 in. Thk at base and tapering down to outer ends, 1.120 in. Between fins
Material:
Iron malleable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A531c0