

View Online at <https://aerobasegroup.com/nsn/5340-00-833-1150>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 3.359 inches and 3.391 inches

**Second Leg Length:**

Between 0.734 inches and 0.766 inches

**Second Leg Width:**

Between 0.609 inches and 0.641 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.297 inches and 0.328 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.234 inches and 0.266 inches

**Second Leg Slot Length:**

Between 0.316 inches and 0.326 inches

**Second Leg Slot Width:**

Between 0.191 inches and 0.201 inches

**First Leg Thickness:**

Between 0.120 inches and 0.130 inches

**Second Leg Thickness:**

Between 0.120 inches and 0.130 inches

**First Leg Width:**

Between 0.609 inches and 0.641 inches

**First Leg Style:**

Square

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One slot

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-529 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0