

View Online at <https://aerobasegroup.com/nsn/5340-00-833-1150>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 3.359 inches and 3.391 inches

Second Leg Length:

Between 0.734 inches and 0.766 inches

Second Leg Width:

Between 0.609 inches and 0.641 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

Second Leg Slot Length:

Between 0.316 inches and 0.326 inches

Second Leg Slot Width:

Between 0.191 inches and 0.201 inches

First Leg Thickness:

Between 0.120 inches and 0.130 inches

Second Leg Thickness:

Between 0.120 inches and 0.130 inches

First Leg Width:

Between 0.609 inches and 0.641 inches

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

90.0 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-529 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0