

View Online at <https://aerobasegroup.com/nsn/5340-00-837-9886>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.990 inches rod connection and 1.010 inches rod connection

Shank Length:

Between 1.115 inches and 1.135 inches

Hole Diameter:

Between 0.2495 inches and 0.2500 inches

Shank Diameter:

0.438 inches

Overall Height:

Between 0.615 inches and 0.635 inches

Overall Width:

Between 0.728 inches and 0.774 inches

Fork Span Width:

Between 0.430 inches and 0.436 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 1.958 inches and 1.978 inches

Fork Arm Thickness:

Between 0.149 inches and 0.169 inches

Fork Depth:

Between 0.552 inches and 0.572 inches

Distance From Pivot Pinhole Center To Fork End:

Between 0.293 inches and 0.333 inches

Thread Size:

0.438 inches rod connection

Material:

Steel comp 4340

Material Specification:

Mil-s-5000 cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

299-099-031, cb2, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-5000 spec.