

View Online at <https://aerobasegroup.com/nsn/5340-00-837-9886>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.990 inches rod connection and 1.010 inches rod connection

**Shank Length:**

Between 1.115 inches and 1.135 inches

**Hole Diameter:**

Between 0.2495 inches and 0.2500 inches

**Shank Diameter:**

0.438 inches

**Overall Height:**

Between 0.615 inches and 0.635 inches

**Overall Width:**

Between 0.728 inches and 0.774 inches

**Fork Span Width:**

Between 0.430 inches and 0.436 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 1.958 inches and 1.978 inches

**Fork Arm Thickness:**

Between 0.149 inches and 0.169 inches

**Fork Depth:**

Between 0.552 inches and 0.572 inches

**Distance From Pivot Pinhole Center To Fork End:**

Between 0.293 inches and 0.333 inches

**Thread Size:**

0.438 inches rod connection

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000 cond c4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

299-099-031, cb2, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-5000 spec.