

View Online at <https://aerobasegroup.com/nsn/5340-00-839-3934>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.560 inches rod connection and 1.620 inches rod connection

Shank Length:

Between 2.110 inches and 2.150 inches

Hole Diameter:

Between 0.3745 inches and 0.3750 inches

Shank Diameter:

0.625 inches

Overall Height:

Between 0.740 inches and 0.760 inches

Overall Width:

Between 1.568 inches and 1.610 inches

End Radius:

Between 0.490 inches and 0.510 inches

Fork Span Width:

Between 1.188 inches and 1.190 inches

Rod Connection Bore Diameter:

Between 0.311 inches and 0.316 inches

Rod Connection Bore Depth:

Between 1.470 inches and 1.530 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 3.430 inches and 3.450 inches

Fork Arm Thickness:

0.190 mils and 0.210 centimeters

Fork Depth:

Between 1.170 inches and 1.190 inches

Thread Size:

0.625 inches rod connection

Material:

Steel comp 4140 or steel

Material Specification:

Mil-s-5626, cond 4 military specification 1st material response or mil-s-5000, cond d1 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

299-099-031, cb1, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-5626 spec.