

View Online at <https://aerobasegroup.com/nsn/5340-00-839-3935>

Thread Class:

3b rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.480 inches rod connection and 1.520 inches rod connection

Shank Length:

Between 0.490 inches and 0.510 inches

Hole Diameter:

Between 0.8743 inches and 0.8746 inches

Shank Diameter:

Between 1.830 inches and 1.850 inches

Overall Height:

Between 1.830 inches and 1.850 inches

Overall Width:

Between 2.930 inches and 2.980 inches

Angle Height:

Between 0.470 inches and 0.530 inches

Fork Span Width:

Between 1.950 inches and 1.960 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 4.980 inches and 5.020 inches

Fork Arm Thickness:

0.490 mils and 0.510 centimeters

Fork Depth:

Between 3.480 inches and 3.520 inches

Thread Size:

1.500 inches rod connection

Angle:

45.0 degrees

Material:

Steel comp 4140 or steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-5626, cond c1 military specification 1st material response or mil-s-5000, cond c1 military specification 2nd material response or mil-s-5000, cond c1 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

299-099-031, cb3, bell helicopter co mfr ref single treatment response

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-5626 spec.