

View Online at <https://aerobasegroup.com/nsn/5340-00-839-4610>

Center To Center Distance Between Bolt Holes Along Width:

Between 4.865 inches and 4.885 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 6.740 inches and 6.760 inches

Wheel Quantity:

1

Tire Size:

3.50x6

Safe Operating Load Rating:

490.0 pounds

Material And Location:

Rubber, soft tread err-100 err-100

Surface Treatment And Location:

Any acceptable

Wheel Type:

Pneumatic tire

Wheel Diameter:

13.000 inches

Effective Height:

Between 17.375 inches and 17.625 inches

Features Provided:

Axle lubrication fitting and swivel lock and swivel lubrication fitting

Plate Style:

Rectangular

Wheel Bearing Type:

Roller or tapered roller

Swivel Bearing Type:

Ball or roller or tapered roller

Swivel Bearing Arrangement:

Two row

Tread Width:

3.500 inches

Caster Plate Length:

8.500 inches

Caster Plate Width:

7.000 inches

Caster Plate Mounting Hole Diameter:

Between 0.652 inches and 0.660 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600