NSN 5340-00-839-9074

Double Angle Bracket - Page 1 of 2

Fabrication Method (non-core):



View Online at https://aerobasegroup.com/nsn/5340-00-839-9074

Stamped
First Leg Length:
0.875 inches
Second Leg Length:
0.938 inches
Second Leg Width:
0.750 inches
Second Leg Corner Radius:
0.250 inches
First Leg Hole Diameter:
Between 0.098 inches and 0.101 inches
Second Leg Hole Diameter:
Between 0.219 inches and 0.233 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.375 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Thickness:
0.072 inches
Second Leg Thickness:
0.072 inches
Center Section Height:
0.750 inches
Center Section Width:
0.750 inches
Center Section Thickness:
0.072 inches
First Leg Width:
0.750 inches
First Leg Corner Radius:
0.250 inches
First Leg Distance Between Hole Centers Along Width:
0.375 inches
First Leg Distance Between First And Second Hole Centers Along Width:
0.188 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
0.188 inches
First Leg Distance From Edge To Hole Center Along Width:
0.188 inches
First Leg Distance From Edge To Hole Center Along Length:
0.188 inches

NSN 5340-00-839-9074

Double Angle Bracket - Page 2 of 2



First Leg Distance Between First And Second Hole Centers Along Length:
0.188 inches
First Leg Distance Between Second And Third Hole Centers Along Length:
0.188 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 2024
Surface Treatment:
Anodize
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0