

View Online at <https://aerobasegroup.com/nsn/5340-00-841-1815>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.125 inches

Second Leg Length:

1.125 inches

Reinforcement Method (non-core):

Web center section

Second Leg Width:

0.750 inches

First Leg Slot Length:

0.250 inches

First Leg Slot Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.438 inches

Second Leg Slot Length:

0.250 inches

Second Leg Slot Width:

0.125 inches

First Leg Thickness:

0.051 inches

Second Leg Thickness:

0.051 inches

Center Section Height:

0.563 inches

Center Section Width:

0.750 inches

Center Section Thickness:

0.051 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.313 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0