

View Online at <https://aerobasegroup.com/nsn/5340-00-850-4763>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.812 inches

Second Leg Length:

0.937 inches

Second Leg Width:

0.688 inches

First Leg Hole Diameter:

Between 0.199 inches and 0.205 inches

Second Leg Hole Diameter:

Between 0.259 inches and 0.265 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

1.523 inches

Center Section Width:

0.688 inches

Center Section Thickness:

0.125 inches

First Leg Width:

0.688 inches

First Leg Distance From Edge To Hole Center Along Width:

0.344 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg End Radius:

0.375 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

125.0 degrees

Second Leg Angle:

125.0 degrees

Special Features:

2nd leg, one corner chamfered 0.250 in. By 40.0 degrees angle

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 1 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-13924 spec.