

View Online at <https://aerobasegroup.com/nsn/5340-00-851-5626>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.355 inches rod connection and 0.375 inches rod connection

**Shank Length:**

Between 0.355 inches and 0.375 inches

**Hole Diameter:**

Between 0.2500 inches and 0.2515 inches

**Shank Diameter:**

0.312 inches

**Overall Width:**

Between 0.678 inches and 0.698 inches

**End Radius:**

Between 0.290 inches and 0.350 inches

**Fork Span Width:**

Between 0.428 inches and 0.448 inches

**Securing Pin Hole Diameter:**

0.047 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.405 inches and 0.445 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 0.860 inches and 0.900 inches

**Fork Arm Thickness:**

0.115 mils and 0.135 centimeters

**Fork Depth:**

Between 0.370 inches and 0.410 inches

**Thread Size:**

0.312 inches rod connection

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ss-8435, united aircraft corp, sikorsky aircraft div mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0