

View Online at <https://aerobasegroup.com/nsn/5340-00-851-5626>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.355 inches rod connection and 0.375 inches rod connection

Shank Length:

Between 0.355 inches and 0.375 inches

Hole Diameter:

Between 0.2500 inches and 0.2515 inches

Shank Diameter:

0.312 inches

Overall Width:

Between 0.678 inches and 0.698 inches

End Radius:

Between 0.290 inches and 0.350 inches

Fork Span Width:

Between 0.428 inches and 0.448 inches

Securing Pin Hole Diameter:

0.047 inches

Distance From Center Of Securing Pin Hole To Rod End:

Between 0.405 inches and 0.445 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 0.860 inches and 0.900 inches

Fork Arm Thickness:

0.115 mils and 0.135 centimeters

Fork Depth:

Between 0.370 inches and 0.410 inches

Thread Size:

0.312 inches rod connection

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ss-8435, united aircraft corp, sikorsky aircraft div mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0