

View Online at <https://aerobasegroup.com/nsn/5340-00-856-0585>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.460 inches rod connection and 0.500 inches rod connection

**Shank Length:**

Between 0.785 inches and 0.805 inches

**Hole Diameter:**

Between 0.1895 inches and 0.1905 inches

**Shank Diameter:**

Between 0.2487 inches and 0.2492 inches

**Overall Height:**

0.375 inches

**Overall Width:**

Between 0.608 inches and 0.652 inches

**End Radius:**

Between 0.209 inches and 0.229 inches

**Fork Span Width:**

Between 0.438 inches and 0.442 inches

**Securing Pin Hole Diameter:**

Between 0.076 inches and 0.086 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.165 inches and 0.205 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 1.592 inches and 1.618 inches

**Fork Arm Thickness:**

0.085 mils and 0.105 centimeters

**Fork Depth:**

Between 0.437 inches and 0.463 inches

**Shank Shoulder Diameter:**

Between 0.340 inches and 0.360 inches

**Shank Shoulder Length:**

Between 0.065 inches and 0.085 inches

**Thread Size:**

0.250 inches rod connection

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond f4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

299-099-031, cc1, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.