

View Online at <https://aerobasegroup.com/nsn/5340-00-856-0867>

**Fabrication Method (non-core):**

Extruded

**First Leg Length:**

Between 0.703 inches and 0.735 inches

**Second Leg Length:**

Between 1.351 inches and 1.367 inches

**Second Leg Width:**

Between 3.742 inches and 3.758 inches

**Second Leg End Width:**

2.874 inches

**First Leg Thickness:**

Between 0.210 inches and 0.215 inches

**Second Leg Thickness:**

Between 0.210 inches and 0.215 inches

**First Leg Width:**

3.694 inches

**First Leg Style:**

Square

**Second Leg Style:**

Square and tapered

**First Leg Angle:**

90.0 degrees

**Special Features:**

Ncircular notch along edge of first leg, 0.625 in. Dia; hole and circular notch in second leg, 0.500 in. Dia. Along with a groove, 0.281 in. Deep and 2.563 in. Long, length of second leg tapers to 0.766 in. Along width

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-200/11, t6 federal specification single material response

**Surface Treatment:**

Oxide film

**Surface Treatment Specification:**

Mil-c-5541, type 1, grade c, class 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.