

View Online at <https://aerobasegroup.com/nsn/5340-00-856-0867>

Fabrication Method (non-core):

Extruded

First Leg Length:

Between 0.703 inches and 0.735 inches

Second Leg Length:

Between 1.351 inches and 1.367 inches

Second Leg Width:

Between 3.742 inches and 3.758 inches

Second Leg End Width:

2.874 inches

First Leg Thickness:

Between 0.210 inches and 0.215 inches

Second Leg Thickness:

Between 0.210 inches and 0.215 inches

First Leg Width:

3.694 inches

First Leg Style:

Square

Second Leg Style:

Square and tapered

First Leg Angle:

90.0 degrees

Special Features:

Ncircular notch along edge of first leg, 0.625 in. Dia; hole and circular notch in second leg, 0.500 in. Dia. Along with a groove, 0.281 in. Deep and 2.563 in. Long, length of second leg tapers to 0.766 in. Along width

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11, t6 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, type 1, grade c, class 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):
Mil-c-5541 spec.