

View Online at <https://aerobasegroup.com/nsn/5340-00-856-6412>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.960 inches and 1.000 inches

Second Leg Length:

2.760 inches

Second Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Slot Length:

Between 0.480 inches and 0.520 inches

First Leg Slot Width:

Between 0.270 inches and 0.290 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Length:

1.380 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg Thickness:

Between 0.073 inches and 0.087 inches

Second Leg Thickness:

Between 0.073 inches and 0.087 inches

First Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.540 inches and 0.580 inches

First Leg End Radius:

Between 0.300 inches and 0.320 inches

Second Leg Side Radius:

0.310 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0