

View Online at <https://aerobasegroup.com/nsn/5340-00-856-6412>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.960 inches and 1.000 inches

**Second Leg Length:**

2.760 inches

**Second Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Slot Length:**

Between 0.480 inches and 0.520 inches

**First Leg Slot Width:**

Between 0.270 inches and 0.290 inches

**Second Leg Hole Diameter:**

0.281 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.380 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.300 inches and 0.320 inches

**First Leg Thickness:**

Between 0.073 inches and 0.087 inches

**Second Leg Thickness:**

Between 0.073 inches and 0.087 inches

**First Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.540 inches and 0.580 inches

**First Leg End Radius:**

Between 0.300 inches and 0.320 inches

**Second Leg Side Radius:**

0.310 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Side radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0