

View Online at <https://aerobasegroup.com/nsn/5340-00-856-6680>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.730 inches rod connection and 1.810 inches rod connection

**Shank Length:**

Between 1.860 inches and 1.940 inches

**Hole Diameter:**

Between 0.256 inches and 0.264 inches

**Shank Diameter:**

0.375 inches

**Overall Height:**

0.500 inches

**Overall Width:**

1.250 inches

**Angle Height:**

Between 0.100 inches and 0.140 inches

**Fork Span Width:**

Between 0.900 inches and 0.980 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 3.150 inches and 3.230 inches

**Fork Arm Thickness:**

Between 0.130 inches and 0.170 inches

**Fork Depth:**

Between 0.840 inches and 0.920 inches

**Thread Size:**

0.375 inches rod connection

**Angle:**

45.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond f military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ps362, the boeing co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.