

View Online at <https://aerobasegroup.com/nsn/5340-00-857-2790>

First Leg Length:

Between 1.960 inches and 2.040 inches

Second Leg Length:

Between 1.960 inches and 2.040 inches

Second Leg Width:

Between 8.190 inches and 8.310 inches

Second Leg Hole Diameter:

Between 0.311 inches and 0.317 inches

Second Leg Distance Between Hole Centers Along Width:

Between 7.105 inches and 7.145 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.440 inches and 0.560 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.400 inches

First Leg Thickness:

Between 0.177 inches and 0.197 inches

Second Leg Thickness:

Between 0.177 inches and 0.197 inches

First Leg Width:

Between 6.820 inches and 6.940 inches

First Leg End Width:

Between 5.580 inches and 6.180 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

Between 0.560 inches and 0.680 inches

Second Leg Cutout Width:

6.000 inches

First Leg Chamfer Angle:

45.0 degrees

Special Features:

When viewing second leg, the hole to the right side is actually a slot which extends to the lower edge of the bracket

Material:

Steel

Material Specification:

Mil-s-13281, clb, gr2 military specification single material response

Surface Treatment:

Primer and enamel

Surface Treatment Specification:

Tt-p-636 federal specification 1st treatment response and mil-e-52798 military specification 2nd treatment response or mil-52835 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-13281 spec.