

View Online at <https://aerobasegroup.com/nsn/5340-00-857-2790>

**First Leg Length:**

Between 1.960 inches and 2.040 inches

**Second Leg Length:**

Between 1.960 inches and 2.040 inches

**Second Leg Width:**

Between 8.190 inches and 8.310 inches

**Second Leg Hole Diameter:**

Between 0.311 inches and 0.317 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 7.105 inches and 7.145 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.440 inches and 0.560 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.360 inches and 0.400 inches

**First Leg Thickness:**

Between 0.177 inches and 0.197 inches

**Second Leg Thickness:**

Between 0.177 inches and 0.197 inches

**First Leg Width:**

Between 6.820 inches and 6.940 inches

**First Leg End Width:**

Between 5.580 inches and 6.180 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Cutout Length:**

Between 0.560 inches and 0.680 inches

**Second Leg Cutout Width:**

6.000 inches

**First Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

When viewing second leg, the hole to the right side is actually a slot which extends to the lower edge of the bracket

**Material:**

Steel

**Material Specification:**

Mil-s-13281, clb, gr2 military specification single material response

**Surface Treatment:**

Primer and enamel

**Surface Treatment Specification:**

Tt-p-636 federal specification 1st treatment response and mil-e-52798 military specification 2nd treatment response or mil-52835 military specification 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-13281 spec.