

View Online at <https://aerobasegroup.com/nsn/5340-00-862-1148>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.880 inches and 0.960 inches

Second Leg Length:

Between 1.880 inches and 1.960 inches

Second Leg Width:

1.180 inches

First Leg Hole Diameter:

0.218 inches

Second Leg Hole Diameter:

0.218 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.590 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.300 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 1.700 inches and 1.780 inches

First Leg Corner Radius:

Between 0.260 inches and 0.300 inches

First Leg Distance Between Hole Centers Along Width:

1.180 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.260 inches and 0.300 inches

Second Leg End Radius:

Between 0.260 inches and 0.300 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0