

View Online at <https://aerobasegroup.com/nsn/5340-00-863-1875>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.070 inches and 1.130 inches

Second Leg Length:

Between 1.090 inches and 1.150 inches

Second Leg Width:

Between 0.720 inches and 0.800 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.219 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.360 inches and 0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.200 inches and 0.220 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 1.150 inches and 1.190 inches

First Leg Corner Radius:

Between 0.200 inches and 0.220 inches

First Leg Distance Between Hole Centers Along Width:

0.750 inches

First Leg Distance Between Hole Centers Along Length:

0.130 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.200 inches and 0.220 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.200 inches and 0.220 inches

Second Leg End Radius:

Between 0.200 inches and 0.220 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0