

View Online at <https://aerobasegroup.com/nsn/5340-00-863-1875>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 1.070 inches and 1.130 inches

**Second Leg Length:**

Between 1.090 inches and 1.150 inches

**Second Leg Width:**

Between 0.720 inches and 0.800 inches

**First Leg Hole Diameter:**

0.281 inches

**Second Leg Hole Diameter:**

0.219 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.360 inches and 0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.200 inches and 0.220 inches

**First Leg Thickness:**

Between 0.057 inches and 0.069 inches

**Second Leg Thickness:**

Between 0.057 inches and 0.069 inches

**First Leg Width:**

Between 1.150 inches and 1.190 inches

**First Leg Corner Radius:**

Between 0.200 inches and 0.220 inches

**First Leg Distance Between Hole Centers Along Width:**

0.750 inches

**First Leg Distance Between Hole Centers Along Length:**

0.130 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.200 inches and 0.220 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.200 inches and 0.220 inches

**Second Leg End Radius:**

Between 0.200 inches and 0.220 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0