## NSN 5340-00-863-5248

Angle Bracket - Page 1 of 2

**Fabrication Method (non-core):** 



View Online at https://aerobasegroup.com/nsn/5340-00-863-5248

Machined
Mounting Hole Type:
Countersunk
First Leg Length:
0.860 inches
Second Leg Length:
1.460 inches
Second Leg Width:
2.000 inches
First Leg Hole Diameter:
Between 0.250 inches and 0.257 inches
Second Leg Hole Diameter:
Between 0.193 inches and 0.199 inches
Second Leg Distance Between Lower Hole Centers Along Width:
1.300 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.650 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.350 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Thickness:
Between 0.130 inches and 0.160 inches
Second Leg Thickness:
Between 0.130 inches and 0.160 inches
First Leg Distance From Edge To Hole Center Along Width:
1.000 inches
First Leg Distance From Edge To Hole Center Along Length:
0.540 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
One hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

## NSN 5340-00-863-5248

Angle Bracket - Page 2 of 2



Material:
Steel comp 4130
Material Specification:
Mil-s-6758, sae, cond f4 military specification single material response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-s-6758 spec.

Mil-std (military Standard):

A042a0