NSN 5340-00-866-7751

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-866-7751

First Leg Length: 0.438 inches Second Leg Length: 1.359 inches Second Leg Width: 0.562 inches Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches First Leg Thickness:
Second Leg Length: 1.359 inches Second Leg Width: 0.562 inches Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
 1.359 inches Second Leg Width: 0.562 inches Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
Second Leg Width: 0.562 inches Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
0.562 inches Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
Second Leg Hole Diameter: 0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
0.128 inches Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
Second Leg Distance Between Hole Centers Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
Second Leg Distance From Edge To Hole Center Along Width: 0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
0.125 inches Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
Second Leg Distance From Edge To Hole Center Along Length: 0.156 inches
0.156 inches
First Leg Thickness:
0.080 inches
Second Leg Thickness:
0.080 inches
First Leg Width:
0.562 inches
First Leg Corner Radius:
0.062 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
No hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Heat Treatment:
H-32 strain hardened
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 federal specification single material response
Surface Treatment:
Chromate

NSN 5340-00-866-7751

Angle Bracket - Page 2 of 2



Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.