## NSN 5340-00-866-8073

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-866-8073

| Cross Sectional Shape:  |
|---|
| Flat  |
| Hole Diameter:  |
| Between 0.196 inches and 0.206 inches   |
| Width:  |
| Between 1.370 inches and 1.410 inches   |
| Edge Shape:   |
| Rectangle, four holes   |
| Length:   |
| Between 1.740 inches and 1.780 inches   |
| Corner Radius:  |
| Between 0.090 inches and 0.120 inches   |
| Distance Between Holes Along Length:  |
| 1.406 inches  |
| Distance Between Holes Along Width:   |
| 1.125 inches  |
| Distance From First Hole Centerline To End Along Length:  |
| Between 0.160 inches and 0.180 inches   |
| Distance From First Hole Centerline To End Along Width:   |
| Between 0.120 inches and 0.140 inches   |
| Body Thickness:   |
| 0.040 inches  |
| Securing Device Type:   |
| Threaded fastener   |
| Mounting Opening Shape Style:   |
| Unthreaded hole   |
| Special Features:   |
| $Center\ hole\ 0.120\ to\ 0.140\ in.\ Dia,\ 0.863\ to\ 0.883\ in.\ Hole\ centerline\ to\ end\ along\ lg,\ 0.653\ to\ 0.683\ in.\ Hole\ centerline\ to\ end\ along\ w$ |
| Material:   |
| Steel   |
| Material Specification:   |
| Mil-s-6721, type 347 military specification single material response  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| A531c0  |
| Mil-std (military Standard):  |

Mil-s-6721 spec.