

View Online at <https://aerobasegroup.com/nsn/5340-00-868-1039>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 1.109 inches and 1.141 inches

Second Leg Length:

Between 2.484 inches and 2.516 inches

Second Leg Width:

Between 73.984 inches and 74.016 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

Between 0.140 inches and 0.150 inches

Second Leg Hole Diameter:

Between 0.196 inches and 0.205 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

9.125 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

9.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

Between 0.110 inches and 0.130 inches

Second Leg Thickness:

Between 0.110 inches and 0.130 inches

First Leg Width:

Between 73.984 inches and 74.016 inches

First Leg Distance Between Hole Centers Along Width:

73.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

135.0 degrees

Special Features:

9 additional mtg holes in smaller end 0.196 in. Min to 0.205 in. Maximum diameter and 6 additional mtg holes in larger end

Heat Treatment:

Annealed

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0