

View Online at <https://aerobasegroup.com/nsn/5340-00-869-4116>

First Leg Length:

3.855 inches

Second Leg Length:

3.855 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Length:

2.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.787 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

2.500 inches

Center Section Width:

3.000 inches

Center Section Thickness:

0.125 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Length:

2.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.787 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Heat Treatment:

Cold worked

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.