

View Online at <https://aerobasegroup.com/nsn/5340-00-869-4116>

**First Leg Length:**

3.855 inches

**Second Leg Length:**

3.855 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

0.281 inches

**Second Leg Hole Diameter:**

0.281 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.787 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

2.500 inches

**Center Section Width:**

3.000 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

3.000 inches

**First Leg Distance Between Hole Centers Along Length:**

2.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.787 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg End Radius:**

0.500 inches

**Second Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius and tapered

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Heat Treatment:**

Cold worked

**Material:**

Steel comp 301

**Material Specification:**

Mil-s-5059 military specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5059 spec.