

View Online at <https://aerobasegroup.com/nsn/5340-00-870-7761>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.625 inches

Second Leg Length:

0.687 inches

Reinforcement Method (non-core):

Rib stiffener center section

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.204 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Width:

0.187 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.438 inches

Second Leg End Radius:

0.438 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Locknut assembly second leg

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t4 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0