

View Online at <https://aerobasegroup.com/nsn/5340-00-870-7761>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

0.625 inches

**Second Leg Length:**

0.687 inches

**Reinforcement Method (non-core):**

Rib stiffener center section

**Second Leg Width:**

0.750 inches

**First Leg Hole Diameter:**

0.204 inches

**Second Leg Hole Diameter:**

0.098 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.187 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg End Radius:**

0.438 inches

**Second Leg End Radius:**

0.438 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Locknut assembly second leg

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4, t4 federal specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0