

View Online at <https://aerobasegroup.com/nsn/5340-00-875-7636>

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Countersunk and threaded

First Leg Length:

Between 0.740 inches and 0.760 inches

Second Leg Length:

Between 0.740 inches and 0.760 inches

Second Leg Width:

Between 0.360 inches and 0.400 inches

First Leg Hole Diameter:

Between 0.1450 inches and 0.1555 inches

Second Leg Hole Diameter:

Between 0.0849 inches and 0.0939 inches

Second Leg Distance Between Hole Centers Along Length:

0.307 mils and 0.317 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.180 inches and 0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg Thickness:

Between 0.180 inches and 0.200 inches

Second Leg Thickness:

Between 0.180 inches and 0.200 inches

First Leg Width:

Between 0.360 inches and 0.400 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.180 inches and 0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.