

View Online at <https://aerobasegroup.com/nsn/5340-00-875-7636>

**Fabrication Method (non-core):**

Machined

**Mounting Hole Type:**

Countersunk and threaded

**First Leg Length:**

Between 0.740 inches and 0.760 inches

**Second Leg Length:**

Between 0.740 inches and 0.760 inches

**Second Leg Width:**

Between 0.360 inches and 0.400 inches

**First Leg Hole Diameter:**

Between 0.1450 inches and 0.1555 inches

**Second Leg Hole Diameter:**

Between 0.0849 inches and 0.0939 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.307 mils and 0.317 centimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.180 inches and 0.200 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.300 inches and 0.320 inches

**First Leg Thickness:**

Between 0.180 inches and 0.200 inches

**Second Leg Thickness:**

Between 0.180 inches and 0.200 inches

**First Leg Width:**

Between 0.360 inches and 0.400 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.180 inches and 0.200 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.