

View Online at <https://aerobasegroup.com/nsn/5340-00-876-2331>

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

4.000 inches

Second Leg Width:

7.875 inches

Second Leg Corner Radius:

0.125 inches

First Leg Hole Diameter:

0.343 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.688 inches

Second Leg Slot Length:

0.562 inches

Second Leg Slot Width:

0.281 inches

First Leg Thickness:

0.119 inches

Second Leg Thickness:

0.119 inches

First Leg Width:

7.875 inches

First Leg Distance Between Hole Centers Along Width:

4.875 inches

First Leg Distance From Edge To Hole Center Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.688 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

3 additional 0.562 in. Lg by 0.281 in. W slots and 4 0.875 in. Lg by 0.281 in. W slots in second leg; incl mtg hardware

Material:

Steel comp 1017

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.