

View Online at <https://aerobasegroup.com/nsn/5340-00-876-2331>

**Fabrication Method (non-core):**

Machined

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

4.000 inches

**Second Leg Width:**

7.875 inches

**Second Leg Corner Radius:**

0.125 inches

**First Leg Hole Diameter:**

0.343 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.688 inches

**Second Leg Slot Length:**

0.562 inches

**Second Leg Slot Width:**

0.281 inches

**First Leg Thickness:**

0.119 inches

**Second Leg Thickness:**

0.119 inches

**First Leg Width:**

7.875 inches

**First Leg Distance Between Hole Centers Along Width:**

4.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.688 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

3 additional 0.562 in. Lg by 0.281 in. W slots and 4 0.875 in. Lg by 0.281 in. W slots in second eg; incl mtg hardware

**Material:**

Steel comp 1017

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-f-14072 spec.