

View Online at <https://aerobasegroup.com/nsn/5340-00-876-3668>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.177 inches and 1.209 inches

Second Leg Length:

Between 1.617 inches and 1.649 inches

Second Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.219 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.290 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg End Radius:

Between 0.420 inches and 0.450 inches

Second Leg End Radius:

Between 0.420 inches and 0.450 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0