

View Online at <https://aerobasegroup.com/nsn/5340-00-876-7367>

First Leg Length:

Between 0.925 inches and 0.965 inches

Second Leg Length:

Between 2.630 inches and 2.690 inches

Second Leg Width:

Between 1.150 inches and 1.210 inches

Second Leg Corner Radius:

Between 0.060 inches and 0.100 inches

First Leg Hole Diameter:

Between 0.245 inches and 0.265 inches

Second Leg Hole Diameter:

Between 0.116 inches and 0.128 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.901 inches and 0.911 inches

Second Leg Distance Between Hole Centers Along Length:

0.901 mils and 0.911 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.120 inches and 0.155 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.107 inches and 0.217 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.260 inches

First Leg End Radius:

Between 0.230 inches and 0.260 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

First Leg Angle:

90.0 degrees

Special Features:

One 0.945 to 0.955 in. Dia. Hole with three equally spaced slots 0.110 to 0.130 in. Wide centrally located between mtg holes in second end

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.