

View Online at <https://aerobasegroup.com/nsn/5340-00-876-7734>

**First Leg Length:**

Between 1.378 inches and 1.382 inches

**Second Leg Length:**

Between 0.630 inches and 0.670 inches

**Second Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Hole Diameter:**

0.2500 inches

**Second Leg Hole Diameter:**

0.2500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg Thickness:**

0.0400 inches

**Second Leg Thickness:**

0.0400 inches

**First Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg End Radius:**

Between 0.360 inches and 0.400 inches

**Second Leg End Radius:**

Between 0.360 inches and 0.400 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

Annealed

**Material:**

Steel comp 302

**Material Specification:**

Mil-s-5059 military specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5059 spec.