

View Online at <https://aerobasegroup.com/nsn/5340-00-880-7677>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

Between 0.780 inches and 0.860 inches

**Second Leg Length:**

Between 3.480 inches and 3.520 inches

**Second Leg End Width:**

2.250 inches

**First Leg Hole Diameter:**

0.190 inches

**First Leg Thickness:**

Between 0.230 inches and 0.270 inches

**Second Leg Thickness:**

Between 1.230 inches and 1.270 inches

**Center Section Height:**

Between 0.230 inches and 0.270 inches

**Center Section Width:**

Between 2.730 inches and 2.770 inches

**Center Section Thickness:**

Between 0.230 inches and 0.270 inches

**First Leg Width:**

Between 2.730 inches and 2.770 inches

**First Leg End Width:**

2.630 inches

**First Leg Distance Between Hole Centers Along Width:**

1.966 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.390 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.200 inches and 0.240 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 1 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-13924 spec.