

View Online at <https://aerobasegroup.com/nsn/5340-00-880-7677>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 0.780 inches and 0.860 inches

Second Leg Length:

Between 3.480 inches and 3.520 inches

Second Leg End Width:

2.250 inches

First Leg Hole Diameter:

0.190 inches

First Leg Thickness:

Between 0.230 inches and 0.270 inches

Second Leg Thickness:

Between 1.230 inches and 1.270 inches

Center Section Height:

Between 0.230 inches and 0.270 inches

Center Section Width:

Between 2.730 inches and 2.770 inches

Center Section Thickness:

Between 0.230 inches and 0.270 inches

First Leg Width:

Between 2.730 inches and 2.770 inches

First Leg End Width:

2.630 inches

First Leg Distance Between Hole Centers Along Width:

1.966 inches

First Leg Distance From Edge To Hole Center Along Width:

0.390 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.200 inches and 0.240 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 1 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-13924 spec.