## NSN 5340-00-881-0196

Rigid Caster - Page 1 of 1

A25600



View Online at https://aerobasegroup.com/nsn/5340-00-881-0196

Contar To Contar Distance Potuson Polt Holes Along Width
Center To Center Distance Between Bolt Holes Along Width:  1.062 inches
Center To Center Distance Between Bolt Holes Along Length: 2.000 inches
Wheel Quantity:
Safe Operating Load Rating:
Not rated
Material And Location:  Steel wheel rim are 100 are 100
Steel wheel rim err-100 err-100
Surface Treatment And Location:
Painted light gray enamel mil-e-15090 formula 3, type 2, class 2 over zinc chromate primer mil-p-6889, wheel rim, body and plate
Wheel Type:
Pneumatic tire
Wheel Diameter:
2.800 inches
Effective Height:
7.780 inches
Features Provided:
Brake lock
Plate Style:
Rectangular
Wheel Bearing Type:
Annular ball
Tread Width:
2.500 inches
Caster Plate Length:
9.000 inches
Caster Plate Width:
6.500 inches
Caster Plate Mounting Hole Diameter:
0.125 inches
Style Designator:
Rigid
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: