NSN 5340-00-881-1006

Double Angle Bracket - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-00-881-1006 |
|---|
| Fabrication Method (non-core): |
| Formed |
| Second Leg Width: |
| Between 0.485 inches and 0.515 inches |
| First Leg Hole Diameter: |
| Between 0.214 inches and 0.224 inches |
| Second Leg Hole Diameter: |
| Between 0.214 inches and 0.224 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| Between 0.240 inches and 0.260 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| Between 0.240 inches and 0.260 inches |
| First Leg Width: |
| Between 0.485 inches and 0.515 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| Between 0.240 inches and 0.260 inches |
| First Leg End Radius: |
| Between 0.344 inches and 0.406 inches |
| Second Leg End Radius: |
| Between 0.344 inches and 0.406 inches |
| First Leg Style: |
| End radius |
| First Leg Hole Arrangement Style: |
| One hole |
| Second Leg Style: |
| End radius |
| Second Leg Hole Arrangement Style: |
| One hole |
| Special Features: |
| Nut brazed in leg |
| Material: |
| Steel comp 410 |
| Material Specification: |
| Ams 5504 assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A042a0