

View Online at <https://aerobasegroup.com/nsn/5340-00-883-6547>

First Leg Length:

Between 0.860 inches and 0.890 inches

Second Leg Length:

Between 1.110 inches and 1.140 inches

Second Leg Width:

Between 0.610 inches and 0.640 inches

First Leg Slot Length:

Between 0.278 inches and 0.288 inches

First Leg Slot Width:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.298 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.328 inches and 0.358 inches

Second Leg Slot Length:

Between 0.403 inches and 0.413 inches

Second Leg Slot Width:

Between 0.322 inches and 0.332 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.610 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.298 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.265 inches and 0.295 inches

First Leg End Radius:

Between 0.485 inches and 0.515 inches

Second Leg End Radius:

Between 0.485 inches and 0.515 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0