

View Online at <https://aerobasegroup.com/nsn/5340-00-883-6547>

**First Leg Length:**

Between 0.860 inches and 0.890 inches

**Second Leg Length:**

Between 1.110 inches and 1.140 inches

**Second Leg Width:**

Between 0.610 inches and 0.640 inches

**First Leg Slot Length:**

Between 0.278 inches and 0.288 inches

**First Leg Slot Width:**

Between 0.200 inches and 0.210 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.298 inches and 0.328 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.328 inches and 0.358 inches

**Second Leg Slot Length:**

Between 0.403 inches and 0.413 inches

**Second Leg Slot Width:**

Between 0.322 inches and 0.332 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 0.610 inches and 0.640 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.298 inches and 0.328 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.265 inches and 0.295 inches

**First Leg End Radius:**

Between 0.485 inches and 0.515 inches

**Second Leg End Radius:**

Between 0.485 inches and 0.515 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0